

NEEDLE VALVE

Stainless Steel, Threaded

AISI 316 PN250
V-MNV-05-11D

Design

Size : Varnasan
Connection : BSP (DIN 259), NPT (ASME B1.20.1)

Technical Features

Working Pressure : PN250
Working Temperature : -40°C / +250°C

Certificate

CE0408, TS EN 10204 3.1, ISO 9001:2015, SIL3

Application

High pressure, hot water, cold water, compressed air-oil



NO	PARÇA ADI	STAINLESS STEEL VALVE
1	BODY	AISI 316
2	CAP	AISI 316
3	SHAFT BEARING	AISI 316
4	SHAFT CLACK	AISI 316
5	SHAFT	AISI 316
6	SHAFT SEALING	PTFE
7	BODY SEALING	PTFE
8	PRESSURE PLUG	STAINLESS
9	HANDLE	AISI 316
10	NUT	STAINLESS

TYPE	SIZE	STAINLESS STEEL VALVE					
		DN	L	H	Dü	Dd	Db
NEEDLE VALVE, THREADED	1/4"	40	75	11,45	13,16	11	
	3/8"	50	75	14,95	16,66	12	
	1/2"	60	75	18,63	20,96	15	
	3/4"	70	75	24,16	26,44	16	
	1"	80	90	30,29	33,25	20	
	1 1/4"	90	125	38,95	41,91	22	
	1 1/2"	100	125	44,85	47,81	22	
	2"	110	125	56,66	59,62	26	

