

## NEEDLE VALVE Stainless Steel, Flanged

AISI 316                      PN250  
V-MNV -05-11F

### Design

Size : EN 558-1  
Connection : EN 1092-1

### Technical Features

Working Pressure : PN250  
Working Temperature : -40°C / +250°C

### Certificate

CE0408, TS EN 10204 3.1, ISO 9001:2015, SIL3

### Application

High pressure, hot water, cold water, compressed air-oil



NO	PART NAME	STAINLESS STEEL VALVE
1	BODY	AISI 316
2	CAP	AISI 316
3	SHAFT BEARING	AISI 316
4	SHAFT CLACK	AISI 316
5	SHAFT	AISI 316
6	SHAFT SEALING	PTFE
7	BODY SEALING	PTFE
8	PRESSURE PLUG	STAINLESS
9	HANDLE	AISI 316
10	NUT	STAINLESS

TYPE	SIZE										
	DN	L	H	D	N	F	b	f	M	MN	Kg
NEEDLE VALVE, FLANGED	15	130	75	95	65	45	16	2	14	M4	1,25
	20	150	75	105	75	58	18	2	14	M4	1,5
	25	160	90	115	85	68	18	2	14	M4	2
	32	180	121	140	100	78	18	2	14	M4	3
	40	200	125	150	110	88	18	3	18	M4	4,5
	50	230	125	165	125	102	20	3	18	M4	6

